

## Eladó Japán fröccsöntő gépek

TOYO Si450III-I450 X 2 sets  
Screw dia: 60mm (2.36")  
Inj Capacity: 763cm<sup>3</sup>  
Inj Speed: 200mm/sec (7.87")  
Inj pressure: 1960Kgf/cm<sup>2</sup>  
Mold Thickness(MAX): 800mm (31.49")  
Tie Bar Clearance: 870 X 870 (34.25" X 34.25")  
MFG year: 2005

TOYO Si450III-J450 X 2 sets  
Screw dia: 68mm (2.67")  
Inj Capacity: 1111cm<sup>3</sup>  
Inj Speed: 200mm/sec (7.87")  
Inj pressure: 1960Kgf/cm<sup>2</sup>  
Mold Thickness(MAX): 800mm (31.49")  
Tie Bar Clearance: 870 X 870 (34.25" X 34.25")  
MFG year: 2005



TOYO Si680IIIW-K600  
Screw Dia: 68mm (2.67")  
Inj Capacity: 1111cm<sup>3</sup>  
Inj Speed: 180mm/sec (7.08")  
Inj pressure: 2156kgf/cm<sup>2</sup>  
Mold Thickness: 1000mm (39.37")  
Tie Bar Clearance: 1145 X 1145 (45.07" X 45.07")  
MFG year: 2005



TOYO Si680IIIW-L750  
Screw Dia: 90mm (3.54")  
Inj Capacity: 2863cm<sup>3</sup>  
Inj Speed: 170mm/sec (6.69")  
Inj pressure: 1862kgf/cm<sup>2</sup>  
Mold Thickness: 1000mm (39.37")  
Tie Bar Clearance: 1145 X 1145 (45.07" X  
45.07")  
MFG year: 2005

